



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension								
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet			
								M	G	G3	M	G	G3	
30A(C)20X163H	20	28,2	56,4	250	3000	56,1	116,7	M27x1,5	G3/4"-A	G3/4"-A				
30A(C)22,2X163H	22,5	31,7	63,5	250	3000	57,6	119,7							
30A(C)25X163H	25	35,3	70,5	250	3000	58,3	121,1							
30A(C)28X163H	28	39,5	79,0	250	3000	60,2	124,7							
30A(C)32X163	32	45,1	75,2	250	2500	62,0	128,3							
30A(C)32X163H	32	45,1	90,2	250	3000	66,5	137,3	M33x1,5	G1"-A	G1"-A	M27x1,5	G3/4"-A	G3/4"-A	
30A(C)36X163	36	50,8	84,6	250	2500	63,5	131,4							
30A(C)36X163H	36	51,3	95,8	250	2800	68,0	140,5							
30A(C)42X163	42	59,9	91,8	230	2300	66,3	137,0							
30A(C)42X163H	42	59,9	99,8	230	2500	70,8	146,1							
30A(C)46X163H	46	65,6	100,5	230	2300	72,7	149,8	M27x1,5	G3/4"-A	G3/4"-A				
30A(C)50X163H	50	71,3	99,8	200	2100	74,5	153,4							
30A(C)55X163H	55	78,4	91,4	200	1750	76,7	157,9							
30A(C)60X163H	60	85,5	99,8	180	1750	78,7	162,4							