

## **HI-PRESS HYDRAULICS Ltd**

## **High Pressure Hand Pump and Accessories**



▼ HPT-1500



- Lightweight and portable high-pressure hand pump
- Two-speed operation displaces a larger volume of oil per stroke, reducing cycle times for many testing applications
- Includes a pressure gauge and coupler for direct connection to **Energac GT-Series Bolt Tensioners**
- Integrated relief valve set at 1500 bar.

## HPT, HT, B Series

Reservoir Capacity:


2,5 litres

Flow at Rated Pressure:


0.61 cm<sup>3</sup>/stroke

Maximum Operating Pressure:

1500 bar







1500 bar ULTRA-HIGH PRESSURE PUMP										
Pump Type	Useable Oil Capacity	Model Number	Pressur	e Rating	g Oil Displacement per Stroke		High Pressure Oil Port with	Ā		
			(bar)		(cm³)		female coupler			
	(litres)		1st stage	2nd stage	1st stage	2nd stage		(kg)		
Two Speed	2,54	HPT-1500	14	1500	16,22	0,61	1/4" BSPP + BR-150	9,0		

1500 bar HOSES						
Model		Hose End 1	Hose End 2	Length		
Number				(m)		
HT-1503		1/4" BSPM	1/4" BSPM	1,0		
		120° Cone	120° Cone			
HT-1510	1,500	1/4" BSPM	1/4" BSPM	3,0		
		120° Cone	120° Cone			
HT-1503HR*		BH-150	BR-150	1,0		
	- 1000 MB - 1400					
HT-1510HR*		BH-150	BR-150	3,0		

1300 bai GOOI ELII3						
Description		Complete Set	Female Half	Male Half		
Quick Disconnect Coupler *		B-150	BR-150	BH-150		
Quick Disconnect Coupler and Adaptor Kit *		BW-150AW	-	-		
Quick Disconnect Blanking Coupler Set *	160 M. 0	B-150B	-	-		

1500 har COUPLERS



**HI-PRESS HYDRAULICS LTD** RIVERSIDE WORKS, FORGE ROAD, WHALEY BRIDGE, HIGH PEAK, SK23 7HY

T: 01663 735089 - F: 01663 735090 T: 01539 734005 - F: 01539 734006 sales@hi-press.co.uk

**HI-PRESS HYDRAULICS LTD** UNIT 2, HALL HOUSE IND EST, NEW HUTTON, KENDAL, CUMBRIA, LAS OAH

cumbria@hi-press.co.uk



<sup>\*</sup> Includes dust caps.

<sup>\*</sup> Includes dust caps.